

Polyethylene Tubing



Low Density Poly Tubing

This film is made from 100% virgin Low density polyethylene which meets LP-378 requirements and has been treated on one side to accept printing. Because it's from virgin polyethylene it can be used for food packaging and service. Tubing can be heat sealed, stapled or taped at either one or both ends. All sizes come on 12" diameter rolls. The approximate roll weight per face inch is 3.4 lbs. The approximate footage per roll is as follows:

| GAUGE | FEET/ROLL | GAUGE | FEET/ROLL |
|--------|-----------|-------|-----------|
| .00125 | 3,500 | .003 | 1,450 |
| .0015 | 2,900 | .004 | 1,075 |
| .002 | 2,150 | .006 | 725 |



Pink Anti-Static Poly Tubing

Economical way to package or enclose objects of same width but various lengths. Can be heat sealed or taped at either one or both ends. Surface resistivity of 10¹² ohms/sq.in. Amine-free, PAS tubing is designed for applications where Faraday Cage Protection is NOT required. All sizes come on 12" diameter rolls. The approximate roll weight per face inch is 3.4 lbs. The approximate footage per roll is as follows:

| GAUGE | FEET/ROLL | GAUGE | FEET/ROLL |
|-------|-----------|-------|-----------|
| .002 | 2,150 | .004 | 1,075 |

Clean Room Tubing

Elkay provides Clean Room Tubing manufactured in a certified class 100 clean room. This stock clean polyethylene tubing is produced from barefoot resin that meets FDA standards, wound on plastic cores and double bagged for added protection.

LOW DENSITY POLY TUBING AVAILABILITY
The black boxes indicate the sizes and gauges available in stock

| LAY FLAT WIDTH INCHES | GAUGE | | | | | |
|--------------------------|---------|--------|-------|-------|-------|-------|
| | 0.00125 | 0.0015 | 0.002 | 0.003 | 0.004 | 0.006 |
| 1.5 | | | | | | |
| 2 | | | | | | |
| 2.5 | | | | | | |
| 3 | | | | | | |
| 4 | | | | | | |
| 4.5 | | | | | | |
| 5 | | | | | | |
| 6 | | | | | | |
| 7 | | | | | | |
| 8 | | | | | | |
| 9 | | | | | | |
| 10 | | | | | | |
| 12 | | | | | | |
| 14 | | | | | | |
| 15 | | | | | | |
| 16 | | | | | | |
| 18 | | | | | | |
| 20 | | | | | | |
| 22 | | | | | | |
| 24 | | | | | | |
| 26 | | | | | | |
| 28 | | | | | | |
| 30 | | | | | | |
| 32 | | | | | | |
| 34 | | | | | | |
| 36 | | | | | | |
| 38 | | | | | | |
| 40 | | | | | | |
| 42 | | | | | | |
| 44 | | | | | | |
| 48 | | | | | | |

PINK ANTI-STATIC POLY TUBING AVAILABILITY
The black boxes indicate the sizes and gauges available in stock

| LAY FLAT WIDTH INCHES | GAUGE | | | | | |
|--------------------------|---------|--------|-------|-------|-------|-------|
| | 0.00125 | 0.0015 | 0.002 | 0.003 | 0.004 | 0.006 |
| 2 | | | | | | |
| 3 | | | | | | |
| 4 | | | | | | |
| 5 | | | | | | |
| 6 | | | | | | |
| 8 | | | | | | |
| 9 | | | | | | |
| 10 | | | | | | |
| 12 | | | | | | |
| 15 | | | | | | |
| 16 | | | | | | |
| 18 | | | | | | |
| 24 | | | | | | |

Low Density Poly Tubing

| ITEM # | WIDTH | GAUGE | APPROX | APPROX |
|----------|--------|---------|-----------|----------|
| .00125 | INCHES | | FEET/ROLL | LBS/ROLL |
| T1-10012 | 10 | 0.00125 | 3500 | 34.0 |
| T1-12012 | 12 | 0.00125 | 3500 | 40.8 |
| T2-14012 | 14 | 0.00125 | 3500 | 47.6 |
| T2-16012 | 16 | 0.00125 | 3500 | 54.4 |
| T2-18012 | 18 | 0.00125 | 3500 | 61.2 |
| T2-20012 | 20 | 0.00125 | 3500 | 68.0 |
| T2-22012 | 22 | 0.00125 | 3500 | 74.8 |
| T2-24012 | 24 | 0.00125 | 3500 | 81.6 |
| T3-26012 | 26 | 0.00125 | 3500 | 88.4 |
| T3-30012 | 30 | 0.00125 | 3500 | 102.0 |
| T3-32012 | 32 | 0.00125 | 3500 | 108.8 |
| T3-36012 | 36 | 0.00125 | 3500 | 122.4 |
| T3-38012 | 38 | 0.00125 | 3500 | 129.2 |
| .0015 | | | | |
| T1-02015 | 2 | 0.0015 | 2900 | 6.8 |
| T1-02515 | 2 1/2 | 0.0015 | 2900 | 8.5 |
| T1-03015 | 3 | 0.0015 | 2900 | 10.2 |
| T1-04015 | 4 | 0.0015 | 2900 | 13.6 |
| T1-05015 | 5 | 0.0015 | 2900 | 17.0 |
| T1-06015 | 6 | 0.0015 | 2900 | 20.4 |
| T1-07015 | 7 | 0.0015 | 2900 | 23.8 |
| T1-08015 | 8 | 0.0015 | 2900 | 27.2 |
| T1-09015 | 9 | 0.0015 | 2900 | 30.6 |
| T1-10015 | 10 | 0.0015 | 2900 | 34.0 |
| T1-12015 | 12 | 0.0015 | 2900 | 40.8 |
| T2-14015 | 14 | 0.0015 | 2900 | 47.6 |
| T2-15015 | 15 | 0.0015 | 2900 | 51.0 |
| T2-16015 | 16 | 0.0015 | 2900 | 54.4 |
| T2-18015 | 18 | 0.0015 | 2900 | 61.2 |
| T2-20015 | 20 | 0.0015 | 2900 | 68.0 |
| T2-22015 | 22 | 0.0015 | 2900 | 74.8 |
| T2-24015 | 24 | 0.0015 | 2900 | 81.6 |
| T3-26015 | 26 | 0.0015 | 2900 | 88.4 |
| T3-28015 | 28 | 0.0015 | 2900 | 95.2 |
| T3-30015 | 30 | 0.0015 | 2900 | 102.0 |
| T3-32015 | 32 | 0.0015 | 2900 | 108.8 |
| T3-36015 | 36 | 0.0015 | 2900 | 122.4 |
| T3-38015 | 38 | 0.0015 | 2900 | 129.2 |
| T3-40015 | 40 | 0.0015 | 2900 | 136.0 |
| T3-42015 | 42 | 0.0015 | 2900 | 142.8 |
| T3-44015 | 44 | 0.0015 | 2900 | 149.6 |
| T3-48015 | 48 | 0.0015 | 2900 | 163.2 |
| ITEM # | WIDTH | GAUGE | APPROX | APPROX |
| .002 | INCHES | | FEET/ROLL | LBS/ROLL |
| T1-01520 | 1 1/2 | 0.002 | 2150 | 5.1 |
| T1-02020 | 2 | 0.002 | 2150 | 6.8 |
| T1-02520 | 2 1/2 | 0.002 | 2150 | 8.5 |
| T1-03020 | 3 | 0.002 | 2150 | 10.2 |
| T1-04020 | 4 | 0.002 | 2150 | 13.6 |
| T1-04520 | 4 1/2 | 0.002 | 2150 | 15.3 |
| T1-05020 | 5 | 0.002 | 2150 | 17.0 |
| T1-06020 | 6 | 0.002 | 2150 | 20.4 |

Elkay has the broadest line of stock poly tubing available anywhere. All stock is available for immediate pick up or delivery.

For quantities over 250 pounds, call for custom quote.

- 100% virgin low density polyethylene
- Treated to allow for printing
- Meets FDA requirements for food use
- Excellent for packaging products of varying lengths
- Supplied on 12" diameter rolls (3" core)



Polyethylene Tubing



Low Density Poly Tubing

| ITEM # | WIDTH | GAUGE | APPROX | APPROX |
|----------|--------|-------|-----------|----------|
| .002 | INCHES | | FEET/ROLL | LBS/ROLL |
| T1-07020 | 7 | 0.002 | 2150 | 23.8 |
| T1-08020 | 8 | 0.002 | 2150 | 27.2 |
| T1-09020 | 9 | 0.002 | 2150 | 30.6 |
| T1-10020 | 10 | 0.002 | 2150 | 34.0 |
| T1-12020 | 12 | 0.002 | 2150 | 40.8 |
| T2-14020 | 14 | 0.002 | 2150 | 47.6 |
| T2-15020 | 15 | 0.002 | 2150 | 51.0 |
| T2-16020 | 16 | 0.002 | 2150 | 54.4 |
| T2-18020 | 18 | 0.002 | 2150 | 61.2 |
| T2-20020 | 20 | 0.002 | 2150 | 68.0 |
| T2-22020 | 22 | 0.002 | 2150 | 74.8 |
| T2-24020 | 24 | 0.002 | 2150 | 81.6 |
| T3-26020 | 26 | 0.002 | 2150 | 88.4 |
| T3-28020 | 28 | 0.002 | 2150 | 95.2 |
| T3-30020 | 30 | 0.002 | 2150 | 102.0 |
| T3-32020 | 32 | 0.002 | 2150 | 108.8 |
| T3-36020 | 36 | 0.002 | 2150 | 122.4 |
| T3-38020 | 38 | 0.002 | 2150 | 129.2 |
| T3-40020 | 40 | 0.002 | 2150 | 136.0 |
| T3-42020 | 42 | 0.002 | 2150 | 142.8 |
| T3-44020 | 44 | 0.002 | 2150 | 149.6 |
| T3-48020 | 48 | 0.002 | 2150 | 163.2 |
| .003 | | | | |
| T1-01530 | 1 1/2 | 0.003 | 1450 | 5.1 |
| T1-02030 | 2 | 0.003 | 1450 | 6.8 |
| T1-03030 | 3 | 0.003 | 1450 | 10.2 |
| T1-04030 | 4 | 0.003 | 1450 | 13.6 |
| T1-05030 | 5 | 0.003 | 1450 | 17.0 |
| T1-06030 | 6 | 0.003 | 1450 | 20.4 |
| T1-07030 | 7 | 0.003 | 1450 | 17.0 |
| T1-08030 | 8 | 0.003 | 1450 | 27.2 |
| T1-10030 | 10 | 0.003 | 1450 | 34.0 |
| T1-12030 | 12 | 0.003 | 1450 | 40.8 |
| T2-14030 | 14 | 0.003 | 1450 | 47.6 |
| T2-15030 | 15 | 0.003 | 1450 | 51.0 |
| T2-16030 | 16 | 0.003 | 1450 | 54.4 |
| T2-18030 | 18 | 0.003 | 1450 | 61.2 |
| T2-20030 | 20 | 0.003 | 1450 | 68.0 |
| T2-22030 | 22 | 0.003 | 1450 | 74.8 |
| T2-24030 | 24 | 0.003 | 1450 | 81.6 |
| T3-26030 | 26 | 0.003 | 1450 | 88.4 |
| T3-28030 | 28 | 0.003 | 1450 | 95.2 |
| T3-30030 | 30 | 0.003 | 1450 | 102.0 |
| T3-32030 | 32 | 0.003 | 1450 | 108.8 |
| T3-34030 | 34 | 0.003 | 1450 | 115.6 |
| T3-36030 | 36 | 0.003 | 1450 | 122.4 |
| T3-38030 | 38 | 0.003 | 1450 | 129.2 |
| T3-48030 | 48 | 0.003 | 1450 | 163.2 |

